

Wireless 1051 anti-intrusion control unit with built-in 4G/IP communicator

1051/020

Product specification:

- Bidirectional radio frequency communication with all devices, ZigBee and 868 MHz connections
- Built-in power supply unit: 230Vac
- Range: 2 km in free range (without reflections and attenuation)
- Internal backup battery with 15 hours duration (average value)
- Radio frequency connection for up to 80 devices
- Full compatibility with ZigBee devices (IR with camera item no. 1051/104A and status LED item no. 1051/003) and 868MHz devices (all current devices)
- Connection of up to 6 IR detectors with camera for alarm verification
- Recording of 3 photos at each alarm event
- Integrated speech synthesis
- Sounder: integrated
- Connections: IP/WiFi/4G
- WiFi mode: client
- Coercion alarm
- Web menu languages: multilingual (Italian, French, German, English)
- Activation/deactivation via remote controls, keyboards, smartphones, tablets
- Three partialisation areas: partial A/B/C insertion
- Assignment of each device to one or more partialisation areas
- Maximum 20 configurable users (codes and remote controls)
- Maximum 10 configurable activation/deactivation/partialisation codes
- Storage capacity: up to 200 events
- Sending of alarms/images, e-mail, SMS, push notifications, CID and SIA protocols
- Remote control via APP (iOS and Android)
- Cycle of 3 vocal calls for each number entered (max. 15 calls)
- Call cycle blocking by selecting key 9 (to be carried out by the called person)
- Integrated keyboard and LCD display
- Measurement of wireless and 4G signals
- Possibility to disable fault signals from the control unit not connected to the Internet via the Disable IP/GSM menu
- Supervision of all devices except remote control and keyboard
- Radio frequency interference detection (Anti Jamming)
- Compatible with Google Home and Alexa
- Compatible with IP camera item no. 1051/004



- Compatible with the current Zeno Portal and MyZeno APP
- Internal sounder sound level: 95dB at 1m
- Operating temperature: -10° to +45°C
- Weight: 600 g
- Dimensions (L x H x D): 260 x 176 x 30 mm

Description

Zeno Pro is the new Zeno control unit version. The most outstanding features introduced in the new version are the new graphics for the web configurator, Wi-Fi connectivity, higher number of manageable devices, multilingual menu, vocal assistant dialogue.

The system is two-directional, flexible and easy to install. It is ideal for all residential environments. Connectivity is one of the fundamental elements of Zeno Pro security: it sends voice alarms, text messages, images, emails, numeric protocols, and notifications.

Supervision, anti-jamming and range signal measurement guarantee the security of Zeno Pro and make the product compliant with EN50131 grade 2 certification.

Logistic data

- Packaging quantity single: **1**
- EAN single: **8021156073207**
- Base: **280 mm**
- Height: **65 mm**
- Depth: **280 mm**