

## Connected kit, Smart Light, Radio Power system

1054/5

### YOKIS HUB

- Power supply: 230 VAC - 50 Hz / 9 VDC power adapter (supplied)
- Power consumption: 1.4W max
- Protection: IP40 (without antenna)
- Range: 250m in free field of view and without obstacles. Reduction of the capacity in the presence of metal elements, crossing of walls or bulkheads
- Weight: 70g (without power adapter)
- Dimensions (LxHxP): 60 x 86 x 27 mm
- MTR2000ERP
- Mains voltage 230 V ~ ( $\pm 15\%$ ) - 50 Hz
- Power: on resistive load 10 A - 250 VAC, max. 2500 VA; other loads 10 A - 30 VDC max 300W
- Consumption
- Ambient temp. - 20 ° C + 60 ° C
- Sound level
- Relative humidity from 0 to 70%
- Range: in the same room
- Frequency: 2.4GHz
- Transmission: Bidirectional with notification LED on the transmitter (If the LED does not flash it is not a malfunction of the batteries, but it means that the radio transmission was unsuccessful) It keeps data in the event of a power failure
- Dimensions (mm) 48 x 33 x 22.5
- MTV500ERP
- Mains voltage: 230V ~ (+ 10% - 15%) - 50Hz
- Power: min. 5VA max. 500VA (300VA in watertight boxes)
- Maximum current: 1.3A / 2.2A watertight boxes: 1.3A / 300VA other boxes: 2.2A / 500VA
- Ambient temperature: -20 ° C + 40 ° C
- Relative humidity: 0 to 90%
- Dimensions (LxHxP): 37 x 46 (+25) x 12 mm



**460,22 Euro (VAT excluded)**  
Price list valid from 01/09/2024

## Description

Smart Luce radio connected kit for controlling lights and actuations: allows you to control 2 ON / OFF actuations and 2 dimming actuations, via YOKIS radio controls and wired buttons, and to connect the system to the Yokis Cloud in order to manage the functions via the Yokis YnO app, both locally and remotely, voice assistants, Alexa and google assistant, and the definition of scenarios, manual or automatic. Ideal as a basic connected kit for controlling the lights in a room or as an extension of

an existing unconnected installation.

Kit consisting of:

- n. 2 cod. 5454462 - Timed electronic step by step relay module, 2000W, Radio Power system, flush-mounted, with neutral
- n. 1 cod. 5454457 - Timed electronic dimmer module, 500W, Radio Power system, flush-mounted, with neutral
- n. 1 cod. 5454495 - YOKIS HUB IP / radio gateway, Radio Power system, to manage the Yokis system locally and remotely via the YnO app

## Logistic data

- Packaging quantity single: **1**
- EAN single: **8021156066216**
- Base: **126 mm**
- Height: **105 mm**
- Depth: **140 mm**