

## Easy Door Controller access control kit with Mifare mini proximity reader with 2-wire bus



1088/301

Product specification: Access control unit item no. 1088/1

- Power supply: 12-30Vdc @ 12-24Vac
- Dimensions (L x H x D): 70 x 16 x 60 mm
- No. of users: 1500 (Local mode) 2000 (Virtual Network mode)
- No. of gates: 1
- No. of proximity readers: 1
- Proximity reader dimensions: (L x H x D): 90 x 47 x 23mm
- Distance between Control unit and Reader: 100m
- System status LED
- no. of event Log: 20,000 (in "Virtual Network" mode only)
- no. of gates managed in "Virtual Network" mode: 50 (one Easy Door Control per gate)

## Description

The kit allows managing a single gate using a Mifare Plus tag. Management of up to 1500 users in local mode. By configuring the control unit of the kit in "Virtual Network" mode, it is possible to manage up to 50 gates and 2000 users without having to connect any cables between the control units. An Encoder 1088/200 connected to your PC is required to program the proximity keys for "Virtual Network" mode. Possibility of having the Event Log in "Virtual Network" mode only.

The kit includes:

- no. 1 item no. 1088/1 - Easy Door Controller, single gate access control unit with Bus system
- no. 1 item no. 1088/41 Mifare Plus Mini Proximity Key Reader with Bluetooth interface, Easy Door Controller, Transit+, 2-wire Bus
- no. 1 item no. 1188/53 Set of 10 Mifare Plus proximity keys

## Logistic data

- Packaging quantity single: **1**
- EAN single: **8021156075881**
- Base: **170 mm**
- Height: **87 mm**
- Depth: **115 mm**