



4CH, H.265 HVR Building&Retail L series, 5M



Product specifications:

- Compression formats: Video: H.265 / H.264 - Audio: G.711a
- Video inputs: 4-CH input with BNC video / 2-CH input with IP video (up to 6-CH with IP video input) (up to 6-CH with mixed video input: Analogue + IP)
- Audio Inputs/Outputs: 4-CH RCA input / 1-CH RCA output
- Recording resolution: 5M Lite(1280x1944)/4M Lite(1280x1440)/1080P(1920x1080)/720P(1280x720)/WD1(960x576)
- Recording frame rate: Main Stream Analog: 5MP-Lite:12fps (per single ch)/4MP-Lite:16fps (per single ch)/1080P:15fps (per single ch)/720P:PAL:25fps(per single ch) /NTSC:30fps (per single ch) IP: PAL:25fps (per single ch) / NTSC: 30fps (per single ch) Substream Analog Max PAL:704x576:10fps (per single ch) NTSC: 704x480:10fps (per single ch)
- IP recording bandwidth: 8Mbps ~24Mbps (default 8Mbps, for each analogue channel excluded, bandwidth increases by approx. 4Mbps)
- Maximum output bandwidth: 48Mbps
- Hard disk interface: Max. 1 SATA HDD (Max 8T)
- HD included: 1000 GB hard disk (default)
- Storage space: External USB device /e-SATA / Network
- Web software / Multilingual client: Internet Explorer 10/11/UVS pro
- Intelligent Video Analysis (for coaxial inputs): PID / LCD / PD / SOUND DETECTION / VIDEO TAMPERING
- Intelligent Video Analysis (*depending on IP camera model): *Perimeter Intrusion Detection (PID), *Line Crossing Detection (LCD), *Stationary Object Detection (SOD), *Pedestrian Detection (PD), *Face Detection (FD), *Cross Counting (CC), Sound Detection, Video Tampering
- Alarm I/O: 4-CH alarm Input, 1-CH alarm Output
- PDA Mobile Software: Urmet iUVS PRO (iOS, Android)
- USB ports: No. 2 -2.0 Ethernet: 1 RJ45 10/100 Base-T
- Network protocols: TCP/IP, DHCP, UDP, Urmet DDNS/UrmetDDNS2 with ID, P2P, PPPOE, Cloud Storage , SMTP , HTTPS , PPPoE , FTP , RTSP , UPNP , SNMP
- BNC output: 1 Out (704x576) Only for SPOT functionality for analogue channels
- VGA output: YES
- HDMI output: YES
- Power consumption: 8.1W (3.6W without HD)
- Power supply: 12V / 2A
- Operating temperature: 0°C~+40°C / below 90%RH
- Cooling fans: NO
- Dimensions (L x H x D): 300 x 53 x 227 mm
- Weight:~3 kg

Description

La gamma HVR (Hybrid Video Recorder) AHD si caratterizza per le funzionalità più avanzate, la compatibilità con le telecamere in tecnologia Analogica, CVI, TVI, AHD e IP, e una straordinaria facilità d'uso, grazie all' intuitivo menu di gestione. Gli HVR sono completamente telegestibili sia da sistemi Windows che MAC, compatibili con il software UVS, il browser, disponibile per IE e Safari , e con l'applicazione gratuita iUVSpro che consente una comoda gestione da tutti gli smartphone e tablet sia Android che iOS. La funzione UTC consente la visualizzazione e la gestione del menù OSD delle telecamere direttamente da HVR.

Logistic data

- Packaging quantity single: **1**
- EAN single: **8021156071371**
- Base: **0 mm**
- Height: **0 mm**
- Depth: **0 mm**