

Wall-mounted transmitter with 4 independent buttons for Zigbee Yokis UP system with white Nea Expì design style for 3-module flush-mounting boxes

4820403

Product Specifications:

- Range: within the same room
- Radio protocol: Zigbee
- Frequency: 2.4 GHz
- Transmission: Bidirectional with notification LED on transmitter
- Battery: CR2032 lithium type
- Average battery duration: 5 years (The battery can be replaced by opening the case with a flat-head screwdriver). Data are retained.
- Number of receivers/channel: 8 in direct mode; unlimited in centralisation/scenario mode
- Operating temperature -10°C to +50°C
- IP54 protection rating
- Relative humidity: maximum 70%
- Dimensions (H x L x D) 88 x 123 x 8.5 mm



103,77 Euro (VAT excluded)
Price list valid from 01/09/2024

Description

The TLM4T503 wall-mounted radio transmitter is a universal radio transmitter with 4 independent channels, capable of controlling all types of Yokis radio receivers (relays, dimmers, roller modules) and third-party lighting devices based on Zigbee 3.0 protocol.

This remote control can be used to manage not only direct commands, but also centralisation and scenario activation commands.

Thanks to the Zigbee radio protocol, it is also possible to transmit commands to modules that are not directly reachable by the transmitter, exploiting the repetition of the command by the actuator modules, and to transmit commands to groups of modules of different types (relays, dimmers, roller actuators, etc.).

It is easy to configure: either by the installer, via the device key or from the UP2Pro App, or by the user, from the YnO UP App.

It is possible to duplicate transmitters by copying the settings of the first one to the subsequent ones, without intervening on the receiver modules.

TLM4T530 is made on Simon Urmet Nea Expì design style in white plastic, compatible with 3-module flush-mounting boxes (support for 503 flush-mounting box included), but can be installed on any flat surface using the supplied double-sided adhesive tape.

The transmitter is powered by a standard CR2032 battery (average battery life greater than 5 years).

Accessories:

A2F (item no. 5454079) - Package of 10 stickers describing the function associated with the button

Logistic data

- Packaging quantity single: **1**
- EAN single: **8021156076895**
- Base: **132 mm**
- Height: **97 mm**
- Depth: **28 mm**